	L #	Hits	Search Text	DBs
1	L1	57	first adj (customer user client node individual agent subscriber) with first adj (code tag label number) and second adj (customer user client node individual agent subscriber) with (second next) adj (code tag label number)	US-PGPUB; USPAT
2	L2	11397	first with (complet$3 finish$3 accomplish$3) with (prior before) with second	US-PGPUB; USPAT
3	L3	0	1 and 2 and @ad<"20010516"	US-PGPUB; USPAT
4	L4	3	1 and (complet$3 finish$3 accomplish$3) with (prior before) and @ad<"20010516"	US-PGPUB; USPAT
5	L5	437	(central center main master) adj (computer mainframe machine node server host) and manual$2 near3 (receipt operat$3) and notification	US-PGPUB; USPAT
6	L6	22	(central center main master) adj (computer mainframe machine node server host) and manual$2 near3 (receipt operat$3) and notification and call$3 and event adj code	US-PGPUB; USPAT
7	L7	17	(central center main master) adj (computer mainframe machine node server host) and manual$2 near3 (receipt operat$3) and notification and call$3 and event adj code and @ad<"20010516"	US-PGPUB; USPAT

	L #	Hits	Search Text	DBs
8	L8	16	(central center main master) adj (computer mainframe machine node server host) and manual$2 near3 (receipt operat$3) and notification and call$3 and event adj code and @ad<"20000626"	US-PGPUB; USPAT
9	L9	26	(central center main master) adj (computer mainframe machine node server host) and (handl$3 manual$2 "not" adj automatically) with (receipt operat$3) and notification and call$3 and event adj code and @ad<"20000626"	US-PGPUB; USPAT
10	L10	27	(central center main master) adj (computer mainframe machine node server host) and (handl$3 human manual$2 "not" adj automatically) with (receipt operat$3) and notification and call$3 and event adj code and @ad<"20000626"	US-PGPUB; USPAT